

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number  
**WO 2005/058398 A1**

(51) International Patent Classification<sup>7</sup>: **A61M 5/34, 5/50**

(21) International Application Number:  
PCT/AU2004/001743

(22) International Filing Date: 9 December 2004 (09.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003906982 16 December 2003 (16.12.2003) AU

(71) Applicant (for all designated States except US): **VON PACE PTY LTD** [AU/AU]; 133 Martin Street, Brighton, 3186 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **AUSTIN, Peter, George** [AU/AU]; 59 New Road, Oak Park, VIC 3046 (AU).

(74) Agent: **SPRUSON & FERGUSON**; GPO Box 3898, Sydney, NSW 2001 (AU).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **RETRACTABLE SYRINGE**



(57) **Abstract:** A retractable syringe (10) having a barrel (40), a needle (72), a hollow plunger (30) and resilient means (80). The barrel (40) has a front end (52), a rear end (54) and defines a receptacle (46) for containing a liquid for injection. The needle (72) is mounted at the front end (52) of the barrel (40). The hollow plunger (30) is movable within the barrel (40) from the rear end (54) to the front end of the receptacle (46) to expel fluid out of the barrel (40) through the needle. The plunger (30) has an inner chamber (34), an axial hole (36) at the front end of the chamber (30) and means (38) blocking the axial hole (36). The resilient means (80) is adapted to urge the needle (72) in a rearward direction into the barrel (40). The resilient means (80) is restrained by an expandable annular member (90) providing a seal at the front end of the receptacle of the barrel (40). The expandable annular member (90) is engaged by a forward part (38) of the plunger (30) when the plunger (30) reaches the front end of the receptacle (46) of the barrel (40). This causes the expandable annular member (90) to move along a surface (116) at the front end of the barrel (40) and expand to release the resilient means (80). The axial hole (36) is then unblocked and the needle (72) is automatically retracted through the axial hole (36) into the inner chamber (34) of the plunger (30). The resilient means (80), in its restrained condition, limits movement of the needle (72) under the above movement of the expandable annular member (90) to release the resilient means (80).

WO 2005/058398 A1